SAFEHOUND* FERROUS WEAPONS DETECTION PORTAL



*Over 352 million guns in circulation

ccording to ATF estimates

*26 U.S. states allow permitless carry and conceal of guns





FERROUS WEAPONS DETECTION PORTAL

TECHNICAL SPECIFICATIONS:

SENSORS (8) total sensors - (6) independent sensors per pole (above head/shoulders/chest/waist/thighs/knees/feet)

DETECTION METHOD Passive ferromagentic detection completely safe (no RF radiation emitted) for pregnant women, pacemakers & medical implants

SYNCHRONIZATION IR motion detection for enhanced false trigger rejection

FLOW RATE Ambient flow rate per lane: 30 people/minute (no weapons detections)

HORIZONTAL RANGE* 48 inches typical using (2) pole portal

VERTICAL RANGE 75 inches (from head to toe)

DETECTION USE CASES Inside visitors' bags, purses, clothing, shoes, hats, wallets, pockets, etc.

Inside uniforms, braziers, shoes, hair, body cavities

Inside suitcases and large package contraband passthrough inspections

ALERTS Omni-directional, daylight-bright cylinder - LED lit from within

Directional blinking color LEDs (zone specific for security personnel)

Integrated audible siren with adjustable alert lengths

Dry trigger contacts for alarms, DVRs, video surveillance, intrusion detection systems, etc.

SECURITY ON/OFF security key lock for all functions

SENSITIVITY 8 levels (user selectable)


SETUP Plug and play out of the box with less than 30 seconds from powering up to full operation. No software or assembly required

POWER 110VAC daily operation & internal rechargable (full charge in 3 hours) 12VDC battery (sealed gel cell) lasts over 24 hours

WEIGHT 17 lbs. fully assembled

DIMENSIONS 68" H x 12" L x 8" W (fully assembled single pole and base unit)

OPTIONS Wall mounting kit, on-site training, extended warranty



All SafeHound units verified using industry-approved non-funtioning weapons security training kit. Ask your BVS sales engineer for details on purchasing optional kit.





